

PRODUCT SPEC PAGE

Collection Name

Grande Restoration

We have always been a company that adores the way time alters and shapes the appearance wood, adding its own special patina over the centuries. Our challenge for this collection was to abbreviate this process while still retaining the classical grace that time lavishes. The most distinctive feature in this collection is the surface undulation typical of grand, ancient European floors. Drawing upon this beauty and tradition we have created the Grande Restoration collection to embody all of the elements of a truly luxurious oak floor. Small board cracks, select knots and occasional soft band saw marks are subtle variations exhibited in this timeless collection. Created with the concept of inheritance, two sub-ranges Castle and Habitat further expand and enrich the Grande Restoration collection in two distinct directions. Castle products play on the idea of inheriting history whereas the Habitat range focuses on inheriting something from the earth.



Product Name

Castle Solid - Unfinished/Unsanded

From - £65 + VAT

Product Information

Pattern Planks	Construction Solid	Profile Straight Edge	Edge Hand Carved	Finish Rough: Unfinished and Unsanded	Installation Glue and Secret Nail	Species European Oak (Quercus Robur)	Origin Europe
-------------------	-----------------------	--------------------------	---------------------	---	---	--	------------------

Product Structure



Solid

Overall Thickness : 21mm-24mm
 Length :18.5cm, 22cm
 Width :1.5m-2.6m
 Where the 80% of the batch is above 2m
 Under Floor Heating :No

N.B. Sizes may change at any time

Sustainability

FSC and PEFC

Optional at extra cost

Timber Neutral

Yes

EUTR

Legally Harvested Timber

Formaldehyde Emission

E1 (0.1ppm): complete compliance with EU safety standards

N.B. We plant 1 tree per every 10m2 you buy. Certification comes as standard.

Grading

Grade : A-D

Maximum Open Filled Knot : Not Filled

Maximum Size of Knots : 8cm

Filled Defects : Open Defects

Sapwood : Allowed

End Checks : No Longer Than Width of Board Allowed (Max 3mm Open)

Filler : No Filler

Colour Variation : Allowed

Filled Crack : Not filled

N.B. The product grading criteria is an approximation. Please allow for variances.

Tests

Slip Testing (to BS 7976-2) : Wet: 29 / Dried: 64

European reaction to fire classification : Cfl-s1

© This technical data sheet was written by The Reclaimed Flooring Company Limited, UK. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Central London, UK

64 Clerkenwell Road
London, EC1M 5PX, UK
+44 (0) 207 250 1108

California, USA

www.reclaimedflooringco.us
212 Marine Street, Suite 100
Santa Monica, CA 90405
+1 (424) 322-9200

Trelleborg, Sweden

Värlinge Gamla Mejeri
Värlingevägen 273-0, 231 94
+46 40 685 06 80

Cheshire, UK

Unit 3 Hammond Trade Centre
Hammond Avenue, Stockport
Cheshire SK4 1PQ, UK
+44 (0) 161 429 9284