

PRODUCT SPEC PAGE

Collection Name

Grande Restoration

We have always been a company that adores the way time alters and shapes the appearance wood, adding its own special patina over the centuries. Our challenge for this collection was to abbreviate this process while still retaining the classical grace that time lavishes. The most distinctive feature in this collection is the surface undulation typical of grand, ancient European floors. Drawing upon this beauty and tradition we have created the Grande Restoration collection to embody all of the elements of a truly luxurious oak floor. Small board cracks, select knots and occasional soft band saw marks are subtle variations exhibited in this timeless collection. Created with the concept of inheritance, two sub-ranges Castle and Habitat further expand and enrich the Grande Restoration collection in two distinct directions. Castle products play on the idea of inheriting history whereas the Habitat range focuses on inheriting something from the earth.



Product Name

Industrial Chic Coastline From - £115 + VAT

Product Information

Pattern	(
Dlanks	

Construction Solid Profile
Tongue and
Groove

Edge Micro Beve

Micro Bevel, Hand Carved Finish Hard Wax Installation
Glue and Secret

Species European Oak (Quercus Robur) Origin Europe

Product Structure



Solid

Overall Thickness: 21mm-24mm

Length :18.5cm, 22cm Width :1.5m-2.6m

Where the 80% of the batch is above 2m

Under Floor Heating: No

N.B. Sizes may change at any time

Sustainability

FSC and PEFC

Optional at extra cost

Timber Neutral

Yes

EUTR

Legally Harvested Timber

Formaldehyde Emission

E1 (0.1ppm): complete compliance with EU safety standards

N.B. We plant 1 tree per every 10m2 you buy. Certification comes as standard.

Grading

Grade :	A-D
Maximum Open Filled Knot :	Not Filled
Maximum Size of Knots :	8cm
Filled Defects :	Open Defects
Sapwood :	Allowed
End Checks:	No Longer Than Width of Board Allowed (Max 3mm Open)
Filler:	No Filler
Colour Variation :	Allowed
Filled Crack :	Not filled

N.B. The product grading criteria is an approximation. Please allow for vairants.

Tests

Slip Testing (to BS 7976-2): Wet: 29 / Dried: 64

European reaction to fire classification: Cfl-s1

© This technical data sheet was written by The Reclaimed Flooring Company Limited, UK. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Central London, UK

64 Clerkenwell Road London, EC1M 5PX, UK +44 (0) 207 250 1108

California, USA www.reclaimedflooringco.us 212 Marine Street, Suite 100 Santa Monica, CA 90405 +1 (424) 322-9200

Trelleborg, Sweden

Värlinge Gamla Mejeri Värlingevägen 273-0, 231 94 +46 40 685 06 80

Cheshire, UK

Unit 3 Hammond Trade Centre Hammond Avenue, Stockport Cheshire SK4 1PQ, UK +44 (0) 161 429 9284